

You want to learn more about us?

Feel free to ask for a meeting on our premises.
Detailed information on the company and on
our product range is also available on-line at
www.huerner.de



10.2025

HÜRNER

SCHWEISSTECHNIK

HÜRNER Schweisstechnik GmbH

Technologie Straße
35325 Mücke

GERMANY

Ph +49 6401 9127 0

E-Mail op@huerner.de
Internet: www.huerner.de

HÜRNER Welding Technology NZ Ltd

12 Croskery Road
Papakura
Auckland 2110
NEW ZEALAND

Ph +64 9 299 3640
Fx +64 9 299 3740

E-Mail: admin@huerner.co.nz
Internet: www.huerner.co.nz

HÜRNER Schweisstechnik Gulf L.L.C

Damascus Street, Al Qusais 4
DUBAI
P.O.Box 233586
UNITED ARAB EMIRATES

Ph +971 4 2584886
Fx +971 4 2584887
E-Mail: sales@hurnergulf.com
Internet: www.hurnergulf.com

Manual 2.0 800-1000-1200

HÜRNER WhiteLine Manual Hydraulic

EN

HÜRNER

SCHWEISSTECHNIK



Stand-alone in Butt-Welding

Technical Specs	160 mm	200 mm	250 mm	315 mm	355 mm	500 mm	630 mm	800 mm	1000 mm	1200 mm
P/N	200-721-160	200-704-200	200-704-250	200-704-315	200-704-355	200-704-500	200-704-630	200-704-800	200-704-1000	200-704-1200
Welding range O.D. (mm)	40–160	63–200	(63) 75–250	90–315	90–355	200–500	315–630	500–800	630–1000	630–1200
Power Supply	230 V 50 Hz	230 V 50 Hz	230 V 50 Hz	230 V 50 Hz	230 V 50 Hz	400 V 50 Hz, 3P	400 V 50 Hz, 3P	400 V 50 Hz, 3P	400 V 50 Hz, 3P	400 V 50 Hz, 3P
Rated power (kW)	2.65	3.45	3.65	4.65	5.4	6.45	11.65	16.8	21.2	23.0
Overall weight with all components (kg)	66	87	109	168	201	295	448	771	1135	1998
Reducer inserts	40, 50, 63, 75, 90, 110, 125, 140	63, 75, 90, 110, 125, 140, 160, 180	(63)*, 75, 90, 110, 125, 140, 160, 180, 200, 225	90, 110, 125, 140, 160, 180, 200, 225, 250, 280	90, 110, 125, 140, 160, 180, 200, 225, 250, 280, 315	200, 225, 250, 280, 315, 355, 400, 450	315, 355, 400, 450, 500, 560	500, 560, 630, 710	630, 710, 800, 900	630, 710, 800, 900, 1000
Welding neck support*)	■	■	■	■	■	■	■	■	■	■
Automatic, "jumping" heating element*)	■	–	■	■	■	■	■	–	–	–
Included standard delivery										
Hydraulic controller for Manual with centralized controls	■	■	■	■	■	■	■	■	■	■
Basic machine chassis	■	■	■	■	■	■	■	■	■	■
Facing tool with micro-switch	■	■	■	■	■	■	■	■	■	■
PTFE-coated heating element	■	■	■	■	■	■	■	■	■	■
Carrying rack	■	■	■	■	■	■	■	■	■	■
HÜRNER transport box for reducers and machine, optional	■	■	■	■	–	–	–	–	–	–
HÜRNER aluminium reducers ¹⁾	■*)	–	■	■	■	■	■	■	■	■
HÜRNER steel reducers ¹⁾	■	■	–	–	–	–	–	–	–	–

¹⁾ Modified design: Screw-Fastened
*) Available as an option

The Manual Hydraulic Series of butt-welding machines in the new WhiteLine generation makes a statement by its superior manufacturing quality and its scalability in the form of an easy upgrade to a data logging-enabled machine with the installation of an SPG 2.0 data logger for welding report generation.

- The machine ships with a hydraulic unit that features, as a unique first, a totally integrated enclosure that also is a splash and dirt shield for all components on the inside. The front panel controls, too, are included in the ingress protection according to the IP 54 rating (where IP 64 is possible upon request).
- All connections, including an additional power socket free to use for the operator's convenience, are located at the back of the controller. Both the facing tool and the heating element are also connected at the back panel of the hydraulic controller. Therefore, no additional power distribution unit is needed.
- The hydraulic unit also doubles as the central control panel of the machine with

which the user performs all relevant settings and process steps. The front panel features a GT keypad, the critical process controls, and also the digital temperature control for the heating element and the extra-large and conveniently readable pressure gauge.

- All HÜRNER Manual Hydraulic butt-welding machines can easily be upgraded with the HÜRNER data logger SPG 2.0 for welding parameter viewing, monitoring, and recording. As a consequence the model version "Manual + SPG" of the butt-welding machine complies with mains gas distributors' specification requirements, which state that data recording and report generation is mandatory, but do not require automatic welding processes.
- The machine chassis is set on a specifically developed support frame exhibiting a warp resistance that manages with ease even the most extreme pipe parameters. Operators can be sure that the machine chassis does not tilt or twist even when very long lengths of pipe with very thick walls are processed.

- Large, knurled turning knobs mean easy handling for the operator who opens or closes the clamps of the machines sized up to O.D. 315. No tools are needed for this.
- The facing tool with integrated micro-safety switch is driven by a high-quality power drive engaged by a transmission chain. The precision heating element ships with a very rugged anti-stick coating.
- A carrying rack is provided for the heating element and the facing tool, to store them with no worries about the heat.
- Maximum protection of the machine, while it is stowed away, is provided (up to O.D. 315) by an optionally available, high-quality transport box that has been specifically designed for the entire machine assembly, with drawer-style storage compartments for the reducer inserts.
- For all machines a welding neck support is of course available, too.

²⁾ Under development

All components are covered by the HÜRNER warranty.




Centralized temperature control



All connections at the back panel of the hydraulic unit



Transport box



Welding neck support

HÜRNER Manual Hydraulic characteristics

Welding monitoring system	Heating element temperature
Display screen	Numeric 7-segment characters, character height 10 mm
Approvals, quality, ingress protection	CE, ISO 9001: 2015, IP 54 (IP 64 optional), WEEE Reg. No. DE 74849106, RoHS-compliant
Hydraulic unit	Only one external power supply needed, all connections and a power socket for the operator's convenience at the back of the enclosure ¹⁾ Digital heating element temperature control, adjustable at the hydraulic unit Hydraulic unit fully enclosed in rugged steel enclosure weighing as little as 19.5 kg (up to O.D. 335 mm) Max. pressure, up to O.D. 355 mm, 130 bar, O.D. 500–630 mm, 150 bar, O.D. 800–1600 mm, 220 bar Accurate and maintenance-free gauge showing the welding pressures Easy upgrade of the hydraulic and control unit with a SPG 2.0 data logger for report generation ■ Pressure sensor 160 bar installable to the hydraulic unit ■ Specifically designed support for construction site-suitable installation of the data logger to the edge of the hydraulics ■ Pressure and temperature lines connected directly to the hydraulic unit with very short lengths of hose or cable ■ Power supply to the data logger from the power socket of the hydraulic unit
Manufacturer warranty	12 months

¹⁾ Only if prepared for SPG data logger